










COSHH ASSESSMENT

PRODUCT NAME:	Multi Primer Filler	MANUFACTURER:	BMW Group
DATE	09/07/2025	STORAGE LOCATION:	Metal Cabinet
PROCESS:	Appy with applicator provided		

CLASSIFICATION OF SUBSTANCES

								
Explosive	Flammable	Gas under pressure	Oxidising	Corrosive	Acute Toxicity	Hazardous to environment	Health Hazard	Health Hazard
<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>

CONTROL MEASURES FOR SAFE USE:

Control Measures

Do not get on skin or clothing. Avoid breathing spray. Do not swallow. Do not get in eyes. Wash skin thoroughly after handling. Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment Keep container tightly closed. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharges. Take care to prevent spills, waste and minimize release to the environment. Do not spray on an open flame or other ignition source.

Storage

Do not store with the following product types: Self-reactive substances and mixtures Organic peroxides Oxidizing agents Flammable solids Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which in contact with water, emit flammable gases Explosives Gase

SIDE EFFECTS

Symptoms

In the case of accident or if you feel unwell, seek medical advice immediately. When symptoms persist or in all cases of doubt seek medical advice.

EXPOSURE LIMITS

Yes

See "Occupational exposure limits" for more details.

PROTECTIVE CLOTHING OR EQUIPMENT (IF ANY) NECESSARY DURING USE:

	Safety Boots		Yes		
	Safety Goggles				
				OTHER	

COSHH ASSESSMENT

THE SUBSTANCE IS HAZARDOUS TO HEALTH WHEN:

In contact with Skin



In contact with Eyes



Breathed in



Swallowed



PRODUCT TYPE

Gas



Vapour



Mist



Fume



Dust



Liquid



Solid



FIRST AID – ACTION TO BE TAKEN IF SUBSTANCE IS:

Swallowed	If swallowed, DO NOT induce vomiting. Get medical attention if symptoms occur. Rinse mouth thoroughly with water.	In Contact with Skin	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention. Wash clothing before reuse
Inhaled	If inhaled, remove to fresh air. Get medical attention	In Contact with Eyes	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lens, if worn. Get medical attention immediately

FIRE PRECAUTIONS:

Extinguishing Media	Water spray Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical	Hazardous combustion products	Carbon oxides Chlorine compounds
Unsuitable extinguishing Media	None	Advice for fire-fighters	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers.

CHEMICAL REACTIONS:

Conditions to avoid Heat, flames and sparks

Materials to avoid. Oxidizing agents

Hazardous decomposition products None

ACCIDENTAL RELEASE MEASURES:

. Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g. by containment or oil barriers). Retain and dispose of contaminated wash water. If spillage enters rivers or watercourses, inform the Environment Agency (emergency telephone number 0800 807060).

DISPOSAL OF THIS PRODUCT

Non-sparking tools should be used. Soak up with inert absorbent material. Suppress (knock down) gases/vapours/mists with a water spray jet. For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent

OCCUPATIONAL EXPOSURE LIMITS

ASSESSOR NAME: